



# MORBARK® BEEVER™ PTO BRUSH CHIPPER



## BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all Morbark equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



### Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders and Vortex chambered air-impeller system provides maximum chipping efficiency.



### Curbside Control Option

The rear-mounted curbside controls allow you to efficiently control the machine from one location with complete view of the infeed and drum areas.



### Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



### Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates 600 lbs. of perpetual down pressure.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

### General

Chipping capacity . . . . . 15"  
Height . . . . . 8'8"  
Width . . . . . 7'3"  
Length . . . . . 17'11"  
Gross weight . . . . . 8,900–9,200 lbs.  
Suspension . . . . . 9,000 lb. torsion  
Infeed opening . . . . . 56" wide x 37" high  
Throat opening . . . . . 20 1/2" wide x 15" high  
Drum . . . . . 23 3/4" wide x 30" diameter  
Engines . . . . . CAT, Cummins, John Deere  
Horsepower . . . . . 130–170 HP  
Fuel capacity . . . . . 31 gallons  
Hydraulic capacity . . . . . 12 gallons  
Frame . . . . . 8.2 lb. 6" channel  
Tires . . . . . (2) 215/75R17 1/2"  
Hitch . . . . . 2 1/2" Pintle

### Equipment Highlights

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and direct drive bottom feed wheel with torque arm coupler

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional pre-plumbed valve section for installation of an aftermarket winch package

5" x 3" tubular steel telescoping drawbar with two 12" extensions

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

### Options

Variable speed flow control  
Folding infeed tray  
Turnbuckle for discharge height adjustment  
Discharge cleanout door on side or bottom  
Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard  
10,000 lb. Torflex suspension axle, electric brakes and break-away actuator with 235/75R 17 1/2", 16-ply radial tires with rims  
Dual 10,000 lb. rear jacks mounted on roadside and curbside  
Custom paint and logo packages  
Knife saver tool  
Engine stop on infeed  
Material pushing tool  
Spanish and English safety decals



877.683.1032

sales | rentals | parts | service

nessturf.com